



Mortuary Refrigerator

+2°C to +8°C

The mortuary refrigerators are developed for the storage of corpses for a short or long period. The units are made of stainless steel for long lasting use. Hydraulic trolley, stainless steel body trolley, autopsy table as well as other accessories to complete the range.

Features:

- ✓ Chamber construction: Fully made of stainless steel
- ✓ Compressor – sealed-type compressor with gas aspiration cooling, complete with total protection motor
- ✓ Digital read-out electronic control panel
- ✓ CFC free insulation and refrigerant
- ✓ Installed with standard LED alarm system



MOT 2B



MOT 3B



MOT 2B- SO



MOT 4B

Model	MOT 2B	MOT 3B	MOT 4B	MOT 2B (Side-open)
Dim. Ext (mm) W x D x H	2500 x 1070 x 1960	2500 x 1070 x 2590	2580 x 2140 x 1960	2550 x 1120 x 1960
Dim. Int (mm) W x D x H	2270 x 860 x 1220	2270 x 860 x 1800	2270 x 1720 x 1220	2270 x 860 x 1220
Door (Swing-out) L x W	2 nos. – 580mm x 860mm	3 nos. – 580mm x 860mm	4 nos. – 580mm x 860mm	2 nos. – 2100mm x 540mm
Stainless Steel Tray	2 nos. – W610mm x L2130mm	3 nos. – W610mm x L2130mm	4 nos. – W610mm x L2130mm	2 nos. – W600mm x L2130mm
Int. & Ext. Chamber	Stainless Steel			
Temp. LED Control	Digital display microprocessor, increment 0.1°C with compressor delay start-up temperature offset for calibration mode, auto defrost high & low alarm			
Standard LED Alarm System	Hi/Low alarm (audio & visual)			
Castor (Heavy Duty)	6 nos.	6 nos.	6 nos.	6 nos.
Door Lock	2 nos.	3 nos.	4 nos.	2 nos.
Internal Air Circulation	Forced-air circulation			
Refrigerant	R407a CFC Free			
Lighting	2pcs	3pcs	4pcs	2pcs
Comp. Recip. Hermetic	3/4 HP	1.0HP	2 x 3/4 HP	3/4 HP
Power Voltage	220Vac 50Hz Single Phase (60Hz for others)			
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 17025			